

Commercial Amplifier

19" x 3.5" x 12.4"
28 lbs



FP - 450 / 650 / 800 / 900

- **Input** XLR Balance & RCA Unbalance @Channel
- **Output** 4-pole SPEAKON & 1 Pair Connect pole @ Channel
- **Front Control** Power Switch , Channel Gain Control
- **Rear Control** Output Switch Mode : Stereo 、 Bridge 、 Parallel
- **Power Supply** Input Sensitivity Switch : 0.775V/1.4V
Plug : 10A, 250V | Cable : CCC 3 x 1.5 mm
- **Protection** Short-circuit Protection, Load Protection, Switch on/off Noise 、 RF Interference



Commercial Amplifier



Spec	FP - 450	FP - 650	FP - 800	FP - 900
4 Ω Stereo	(@Channel) 600W	(@Channel) 900W	(@Channel) 1200W	(@Channel) 1350W
8 Ω Stereo	(@Channel) 400W	(@Channel) 600W	(@Channel) 800W	(@Channel) 1000W
8 Ω Mono	1200W	1800W	2300W	2700W
Gain Power	31 dB	33 dB	34 dB	36 dB
Size	482 x 89 x 315 mm	482 x 89 x 315 mm	482 x 89 x 315 mm	482 x 89 x 366 mm
Net Weight	12.7 kg	13.5 kg	14.5 kg	19.5 kg
Shipping Weight	14.7 kg	15.5 kg	16.5 kg	21.5 kg
Freq. Response	20Hz ~ 20kHz, +0/-1 dB			
THD	<0.5%, 20Hz ~ 20kHz			
Modulation	≤0.35%			
Slew rate	>10V/μs			
Damping Ratio	>200			
S/N Ratio	>100 dB			
Crosstalk	@ 1kHz : -75 dB @ 20kHz : -59 dB			
Input Sensitivity	0.775V or 1.4V			
Input Impedance	Balance : 20K Ω Unbalance : 10K Ω			

