



Digital Conference System | FCS Series

with LCD Display showing operation modes and speaking statuses

F C S - 6 3 1 5

Table-Top Chairman Unit



FCS-6316
Table-Top
Delegate Unit

- DSP chip: sensitivity adjustment for each microphone
- 2 x 24 digit LCD display to show operation modes and speaking statuses
- Built-in 2.5" x 1.5" Hi-Fi speaker and voting interface with five buttons in the lid
- 2 sets of Ø3.5mm recording plugs
- No limitation of chairman unit's quantity and the position and sequence can be randomly set



Build-in Speaker

Unit size	2.5"
Capacity	0.5W
MSP	≥120

SPECIFICATION

Frequency Response	100HZ~16KHZ
Sensitivity	≥ -50dB
T.H.D.	≤ 0.1%
S/N Ratio	≥ 70dB
Supply Voltage	DC 12V~18V
Audio Indicator	3Colours LED illuminated bar. Red Indicates
Connection	RJ-45 Plug x 2 (2.5M / 20M Cat 5e)
Gain Control	(AGC) -45~0dB
Audio Jack	3.5ø Stereo
REC Jack	3.5ø Stereo
Dimension (HxWxD)	53.6×169.3×131.8 mm
Weight	877g
Base	Zinc-Aluminum Alloy Diecast & Anti-slip mat



Digital Conference System | FCS Series

with LCD Display showing operation modes and speaking statuses

F C S - 6 3 1 6

Table-Top Delegate Unit



FCS-6315
Table-Top
Chairman Unit

- DSP chip: sensitivity adjustment for each microphone
- 2 x 24 digit LCD display to show operation modes and speaking statuses
- Built-in 2.5" x 1.5" Hi-Fi speaker and voting interface with five buttons in the lid
- 2 sets of Ø3.5mm recording plugs
- Microphone auto-off as 10-99 seconds after the speaker finish speaking



Build-in Speaker

Unit size	2.5"
Capacity	0.5W
MSP	≥120

SPECIFICATION

Frequency Response	100HZ~16KHZ
Sensitivity	≥ -50dB
T.H.D.	≤ 0.1%
S/N Ratio	≥ 70dB
Supply Voltage	DC 12V~18V
Audio Indicator	3Colours LED illuminated bar. Red Indicates
Connection	RJ-45 Plug x 2 (2.5M / 20M Cat 5e)
Gain Control	(AGC) -45~0dB
Audio Jack	3.5ø Stereo
REC Jack	3.5ø Stereo
Dimension (HxWxD)	53.6×169.3×131.8 mm
Weight	877g
Base	Zinc-Aluminum Alloy Diecast & Anti-slip mat