

# UHF Tour Guide System (Transmitter)

2.24" x 3.23" x 0.75"  
0.13 lbs

# SENRUN®

U T - 9 6

With 3.5 mm Tie-clip Microphone | Neck strap



U R - 9 6  
Receiv er

- **Work with UR-96**  
Channel is selected by up and down button
- **LED Display**  
Show the battery status, channel and signal strength
- **Volume Control**  
Unit can adjust the volume

© Sunrise Trading Company



## SPECIFICATION

<b>Microphone</b>	Condenser
<b>Oscillation Mode</b>	UHF PLL synthesized controlled
<b>Frequency Range</b>	600 ~ 960 MHz
<b>Channels</b>	1 to 16 PLL
<b>Spurious Emission</b>	<-50 dB
<b>RF power</b>	<10 mW
<b>Stability</b>	±0.005%
<b>T.H.D</b>	<0.5% (@ 1kHz)
<b>Frequency Response</b>	100Hz ~ 15kHz (±3dB)
<b>Audio Input</b>	3.5 mm AUX IN
<b>Available Distance</b>	70 m
<b>Power Consumption</b>	60 mA ±10 mA
<b>Battery</b>	AAAx2 (UM-4)
<b>Battery life</b>	6 ~ 8 hours (rechargeable battery)
<b>Dimensions</b>	57 x 82 x 19 mm
<b>Weight (approx.)</b>	60 g

# UHF Tour Guide System (Receiver)

2.24" x 3.23" x 0.75"  
0.13 lbs

# SENRUN®

U R - 9 6

With 3.5 mm Earphone | Neck strap



U T - 9 6  
Transmitter

- **Work with UT-96**  
Channel is selected by up and down button
- **LED Display**  
Show the battery status, channel and signal strength
- **Volume Control**  
Unit can adjust the volume



## SPECIFICATION

<b>Oscillation Mode</b>	UHF PLL synthesized controlled
<b>Frequency Range</b>	600 ~ 960MHz
<b>Channels</b>	1 ~ 16
<b>S/N ratio</b>	80 dB overall
<b>Sensitivity</b>	-90 dBm ±2 dBm
<b>Modulation</b>	±40 kHz
<b>Stability</b>	±0.005%
<b>T.H.D</b>	< 0.5% (@ 1kHz)
<b>Frequency Response</b>	100Hz ~ 15kHz (±3dB)
<b>Audio Output</b>	3.5 mm AUX OUT
<b>Available Distance</b>	70 m
<b>Power Consumption</b>	90 mA ±10 mA
<b>Battery</b>	AAAx2 (UM-4)
<b>Battery life</b>	6 ~ 8 hours (rechargeable battery)
<b>Dimensions</b>	57 x 82 x 19 mm
<b>Weight (approx.)</b>	60 g