

Infrared Pendant Microphone

Infrared Microphone System

3.66" x 1.20" x 0.75"
0.086 lbs

Linkx

T - 6



External Aux Input
for line or Mic input

Volume Control
High / Middle / Low Switch

Power Switch
On / Off / Mute Push Button

With a built-in breath filter, T6 can function as a pass-around hand mic.

Micro-USB receptacles and convenience charger solution, allows T6 to charge from laptop pc or AC outlet by the accompanied USB to micro-USB extension cord and power adaptor.



SPECIFICATION

Type	Pendant
Infrared Ray Wavelength	850 nm
Transmission Frequency	1- channel A : 2.08 MHz 2- channel B: 2.54 MHz 3- channel B: 2.54 MHz (push to talk)
Modulation	FM
Pilotone Frequency	32.768KHz
Transmission Angle	180°, Conical
Microphone Capsule	>Condenser, Unidirectional
Location of IR Emitter	Built-in, Top
External Aux Input	One 3.5mm Stereo Jack
Function Control Switch	Aux Input Volume Up Aux Input Volume Down
Current Consumption	90mA
Battery Used	Linkx Li-Polymer Battery (3.7V / 600mAh)
Battery Life	Approx. 7 hours
External Power Charge	DC+5V , Micro USB connecter
Clip and Lanyard	Clip and Adjustable neck strap with break away clip
Dimensions	19 (Thickness) × 93 (H) × 30.6 (W) mm
Weight	Approx. 39 g (with Battery)