UHF Wireless Microphone System

MASCOT

Wireless Microphone Receiver + Wireless Microphone Combo Set



- RS-221 Wireless Mic. Receiver Combo Options:
 A:2 x UF-18 Handheld Microphone
 B:1 x UF-18 Handheld Microphone + 1 set UT-62
 C:2 x UT-62 Bodypck Transmitter with Mic set
- UT-62 Bodypack Transmitter with Headset Mic OR Tieclip Mic





Handheld



UT-62 Bodypack

SPECIFICATION

Frequency Response 80Hz to 18KHz
Bandwidth 30MHz

Dynamic Range >100dB

Frequency Range UHF520~937.5MHz

Frequency Stability ± 0.005%

Modulation FM ±20KHz

Modulation FM ±20KHz
Oscillator PLL Synthesized
S/N Ratio >100dB, 20KHz of

>100dB, 20KHz deviation & 60dBµV antenna input

T.H.D. 1% (at 1KHz) **Tone Signal** 32.768KHz

Dimension W 420 x H 45 x D 180 mm

UHF | **Dual Channel** | **Wireless Microphone Receiver**

MASCOT

Wireless Microphone Receiver

W 420 x H 45 x D 180 mm

R S - 2 2 1

- UHF Diversity receiver, 16 available frequency for quickly set-up
- · Dual Channel, with 2 UF-18 handheld Microphone
- · Adjustable squelch for eliminating RF inference
- Up to 60 meters reception range for total wireless freedom
- Made in Taiwan

© Sunrise Trading Company



Up to 4 systems can be used simultaneous and 8 wireless microphones

SPECIFICATION

Channel Dual
Case 19"EIA Rack Case
Receiving Mode Diversity
Channel Select Tact Switch
Image & Spurious Minimum 70dB

Rejection

Receiving Sensitivity $\,$ At 3 μV over 52dB S/N Ratio

Selectivity > 50dB

1: 243.95MHz / 2: 10.7MHz

Audio Output Unbalanced
Power Supply DC12V/230±10mA

© Sunrise Trading Company

UHF | Handheld Microphone | Bodypack Transmitter

MASCOT

Wireless Microphone Receiver

UF-18 @ 260 x 52φ mm UT-62 @ 65 x 100 x 27 mm

8 U F

 UT-62 Bodypack Transmitter with Headset Mic OR Tieclip Mic





6

SPECIFICATION

Channel Select Rotary **RF Power Output** 10mW (Max.) **Frequency Stability** ±0.005% **Spurious Emission**

>60dB below carrier frequency Battery DC3V (1.5V x 2AA batteries) 32.768KHz

Tone Key **Current Consumption** 120 ± 10mA

Dimension(WxHxD)

UF-18 @ 260 x 52φ mm UT-62 @ 65 x 100 x 27 mm