

Portable PA Amplifier

Shoulder strap type

(HxWxD) 11.42" x 6.30" x 8.27"

7.06 lbs with battery

E P - 3 0 0

SENRUN®

ALTERNATIVE OPTION

*Belt-pack Transmitter with Tie-clip microphone
or Headset microphone*



U P L - 8 3
Transmitter

B M - 3 0 6
Tie - clip

H M - 2 2
Headset



ALSO IN THE BOX

Charging Cable x 1

Storage Bag x 1



Handheld Microphone x 1~2

(OPTIONAL)



FEATURES

Lead-acid battery with built in smart charger system
Approximately 4.5 hours to reach full capacity

USB and AUX IN/OUT 3.5mm connector
plug in and play any audio file

UHF PLL 16 channels
support handheld mic. or bodypack transmitters

5 different tones mode options



SPECIFICATION

Speaker	5.25" 4Ω Full range
Output power	50W @Peak / 35W @RMS / 4Ω Load
Receiver Module	UHF PLL Single receiver module 16 selectable channel
Frequency range	UHF 600-960 MHz
Frequency response	50Hz -20KHz ± 3dB
T.H.D	<1%
Charge time	approx. 4.5 hours
Battery life	Up to 8 hours (depends on volume)
Power supply	100 -240V AC switching power supply Lead acid battery 12V/2.7Ah
Dimensions	W 160 x H 290 x D 210 mm
Weight (approx.)	3.2 kg (with battery)



Shoulder strap type



EP-580

60W @Peak / 42W @RMS / 4Ω Load
Stand-by **10~12 hours** / Battery life
Up to 8 hours (depends on volume)

(DxWxH) **325x180x230 mm**
approx. 2.9 kg (with battery)



EP-350

50W @Peak / 35W @RMS / 4Ω Load
Stand-by **10~12 hours** / Battery life
Up to 8 hours (depends on volume)

(DxWxH) **210x160x290 mm**
approx. 2.2 kg (with battery)



EP-300

50W @Peak / 35W @RMS / 4Ω Load
Stand-by **10~12 hours** / Battery life
Up to 8 hours (depends on volume)

(DxWxH) **210x160x290 mm**
approx. 3.2 kg (with battery)