# **Portable PA Amplifier**



Shoulder strap type

(HxWxD) 12.80" x 7.09" x 9.06" 6.39 lbs with lithium battery

E P - 5 8 0

### **ALTERNATIVE OPTION**

Belt-pack Transmtter with Tie-clip microphone or Headset microphone



UPL-83 Transmitter BM-306 Tie-clip H M - 2 2
H e a d s e t



### **ALSO IN THE BOX**

Lithium Battery x 1

Charging Cable x 1

Storge Bag x 1



Handheld Microphone x 1~3

(OPTIONAL)

Remote Control x 1

# **FEATURES**

Using one transmitter (microphone) can broadcast to multiple EP-580 (same channel and frequency)

Electricity power 4 stage display indicates the recharge and battery status

LCD display shows track name and status in either English or Chinese

Support to 32GB memory card device Support USB device and SD card

Remote control function
Digital echo with adjust function



# **SPECIFICATION**

**Speaker** 1" tweeter

5.25" woofer

**Output power**  $60W(Max) \mid 42W(RMS) / 4\Omega Load$ 

**Receiver Module** UHF PLL Non- diversity receiver module

**Frequency range** UHF 600-960 MHz **Frequency response** 30Hz -20KHz ± 3dB

**T.H.D** <1%

**Charge time** approx. 4.5 hours

**Battery life** Up to 8 hours (depends on volume) **Power supply**100 -240V AC switching power supply

Lithium battery 14.4V/2.6Ah

**Dimensions** 180 x 325 x 230mm (W x H x D)

**Weight** approx. 2.9 kg (with battery)



# Shoulder strap type



**EP-580** 

60W @Peak / 42W @RMS / 4Ω Load Stand-by 10~12 hours / Battery life Up to 8 hours (depends on volume)

(DxWxH) **325x180x230 mm approx. 2.9 kg** (with battery)



EP-350

50W @Peak / 35W @RMS / 4Ω Load Stand-by 10~12 hours / Battery life Up to 8 hours (depends on volume)

(DxWxH) **210x160x290 mm approx. 2.2 kg** (with battery)



**EP-300** 

50W @Peak / 35W @RMS / 4Ω Load Stand-by 10~12 hours / Battery life Up to 8 hours (depends on volume)

(DxWxH) **210x160x290 mm approx. 3.2 kg** (with battery)