## **Bass Reflex | 2-Way Ceiling Loudspeaker**

Public Address Series

ø7.48" x H5.12" 3.59 lbs

C S B - 3 1 5 0

Very high quality 2-way speaker system with 3.5" polypropylene bass/mid cone & 8-ounce magnet + 0.5" mylar laminate dome tweeter


- √ 100 Hours Life Tested
- ✓ CE Certified (EMC & LVD)
- ✓ EASE Data
- ✓ RoHS Compliance
- ✓ Withstanding/Insulation Tested

## Front Side

- Bass reflex design. Ported enclosure for extended bass response. Compact foreground and sound reinforcement quality.
- Rotary power selector. Removable locking connector with screw-down terminals, 2 input terminals and 2 loop-thru output terminals







## **SPECIFICATION**

Rated Power (rms) 15W

 Impedance
 667Ω, 1.33kΩ, 2.67kΩ, 5.33kΩ & 8Ω 

 Power Taps @ 100V
 15W, 7.5W, 3.75W, 1.9W & 8Ω 

 Power Taps @ 70V
 7.5W, 3.75W, 1.9W, 1W & 8Ω

**SPL (1W / 1m)** 86dB **Max. SPL (Rated W / 1m)** 98dB

Frequency Range (-10dB)  $85 \text{ Hz} \sim 25 \text{k Hz}$ Dispersion 1k Hz / 4k Hz  $210^{\circ}$  /  $140^{\circ}$ Operating Temperature  $-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$ Power Selection Selecting switch

**Termination** Removable locking connector with

screw-down terminals, 2 input terminals and 2 loop-thru output terminals

Material Baffle: High impact ABS, Backcan: Steel

Colour / Finish White

Dimensions Dia. 190 X H 130 mm
Cutout Size Dia. 170 mm
Net Weight (ea) 1.63 kg

**Mounting** Rotating mount tabs

© Sunrise Trading Company